



TECHNICAL DATA SHEET  
V102020

# XTEC 5W40 C3

## DESCRIPTION

Fuel economy synthetic engine oil formulated from last generation additives and specially developed for vehicles equipped with a particle filter (DPF), conforming to the EURO IV et EURO V norms.

## APPLICATION

**Bardahl XTEC 5w40 C3** has been developed according to the Mid S.A.P.S/high HTHS technology, ensuring a high protection of the engine. It is compatible with petrol and diesel engines, equipped or not with a turbo, of MERCEDES, BMW, RENAULT NISSAN DACIA, VW, AUDI, SEAT, SKODA, FORD passenger cars and delivery vans. Particularly recommended for diesel engines with a direct injection pump.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	C3
API	SN / SN+
VW	505.00/505.01
MERCEDES-BENZ	MB 229.51 / MB 229.31 / MB 226.5
PORSCHE	A40
BMW	Longlife-04
FORD	M2C917-A
RENAULT	RN0700/RN0710
GM	Dexos 2
FIAT	9.55535-S2 / GH2

## PROPERTIES

- ✓ Avoids fuel overconsumption,
- ✓ Forms a lubricating film protecting the engine at high temperature,
- ✓ Extends the drain intervals,
- ✓ Makes cold starting easier,
- ✓ Provides a high protection against corrosion and wear.

### SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)



TECHNICAL DATA SHEET  
V102020

TECHNICAL DATA

Density at 20°C	Kg/l	0,850
Viscosity at -30°C	mPa.s	5500
Viscosity at 40°C	mm <sup>2</sup> /s	82,8
Viscosity at 100°C	mm <sup>2</sup> /s	14,0
Viscosity index		175
Flash point COC, °C	°C	232
Pour point, °C	°C	-42
TBN alcalinity	mgKOH/g	7,4
Sulphated ash contents	%	0,77

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36341	12 x 1 L
36342	4 x 4 L
36343	3 x 5 L
36348	20 L
36344	60 L
36347	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com