



XTEC TRUCKS 10W40

DESCRIPTION

Synthetic oil made from last generation performance additives and formulated for heavy diesel engines (trucks, busses and delivery vans) to reduce friction, eliminate sludge and optimize fuel consumption. It is based on the LOW SAPS (very low ash contents) technology to ensure an extended lifespan and a good functioning of post-treatment exhaust systems (DPF).

APPLICATION

Bardahl XTEC Trucks 10w40 offers an excellent stability and a high resistance to temperatures to avoid the formation of deposits in the engine and make cold start easier.

SPECIFICATIONS

This product offers the following performance level:

ACEA	E7/E6
API	CI-4
MB	228.51
RENAULT VI	RXD/ RGD/ RLD-2
DEUTZ	DQC IV-10 LA
VOLVO	VDS-3
DAF	Long Drain
MACK	EO-N
MAN	M3477/ M3271-1
MTU	Type 3.1
CUMMINS	CES 20076/ 20077
JASO	DH-2
KAMAZ	Euro 1,2,3,4
NATO=code	O-1180
TL	9150-0107/3





PROPERTIES

- ✓ Helps to extend the lifespan of particle filters,
- ✓ Offers high detergency properties and avoids the formation of deposits,
- ✓ Provides strong dispersion properties,
- ✓ Is highly resistant to corrosion and oxidation,
- ✓ Provides anti-wear and anti-foam properties,
- ✓ Has a low ash contents.

TECHNICAL DATA

Density at 15°C	Kg/l	0,863
Viscosity at -35°C	mPa.s	6120
Viscosity at 40°C	mm ² /s	95,9
Viscosity at 100°C	mm ² /s	14,3
Viscosity Index		154
Flash point COC, °C	°C	223
Pour point, °C	°C	-39
TBN alcalinity	mgKOH/g	10,1
Sulphated ash contents	%	0,95

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36218	20 L
36214	60 L
36217	205 L