

XTEC TRUCKS 5W30

DESCRIPTION

Synthetic oil made from last generation performance additives and formulated for heavy diesel engines (trucks, busses and delivery vans) to reduce friction, eliminate sludge and optimize fuel consumption, « **Fuel Economy** ». It is based on the LOW SAPS (very low ash contents) technology to ensure an extended lifespan and a good functioning of post-treatment exhaust systems (DPF).

APPLICATION

Bardahl XTEC Trucks 5w30 offers an excellent stability and a high resistance to temperatures to avoid the formation of deposits in the engine and make cold start easier. For intensive use in all seasons, in engines EURO 4, EURO 5, EURO 6, ideally in combination with a good diesel fuel with a low sulphur.

SPECIFICATIONS

This product offers the following performance level:

ACEA	E6, E7, E9
API	CJ-4 / SN
MB	228.31/ 228.51
RENAULT VI	RLD-3
DEUTZ	DQC IV-10 LA
VOLVO	VDS-3 / VDS-4
SCANIA	Low Ash / LDF-4
MACK	EO-O Premium Plus/ EO-N, EO-M Plus
MAN	M3677/ M3477/ M3271-1
MTU	Type 3.1
CUMMINS	CES 20081
CAT	ECF-3
DETROIT DIESEL	93K218
JASO	DH-2
VOITH	class B



PROPERTIES

- ✓ Helps to extend the lifespan of particle filters,
- ✓ Offers high detergency properties and avoids the formation of deposits,
- ✓ Provides strong dispersion properties,
- ✓ Is highly resistant to corrosion and oxidation,
- ✓ Provides anti-wear and anti-foam properties,
- ✓ Has a low ash content.

TECHNICAL DATA

Density at 15°C	Kg/l	0,855
Viscosity at -30°C	mPa.s	6460
Viscosity at 40°C	mm ² /s	70,2
Viscosity at 100°C	mm ² /s	11,8
Viscosity Index		165
Flash point COC, °C	°C	214
Pour point, °C	°C	-45
TBN alcalinity	mgKOH/g	9,3
Sulphated ash contents	%	0.99

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36578	20 L
36574	60 L
36577	205 L