



XBF DOT 4 BRAKE FLUID

DESCRIPTION

Fully synthetic brake fluid, high performance, formulated from glycol ethers.

APPLICATION

BARDAHL XBF DOT4 meets all the international requirements mentioned below.

It is formulated to ensure good systems safety and protection, for high dry and wet boiling point.

Thanks to its good technical specifications, BARDAHL XBF DOT4 is a high-quality brake fluid and can be used universally in brake systems from old and new generations.

BARDAHL XBF DOT4 are composed of additives that ensure a great chemical stability.

Can be used in standard drums and in complex systems of disc brakes.

Is miscible in DOT3, DOT4 and DOT5.1, **but cannot be used with silicone-based fluid.**

SPECIFICATIONS

FMVSS 116	DOT 4
ISO	4925 Class 4
SAE	J1703

CLASSIFICATION

Refer to safety data sheet.

- High performance brake fluid with a high boiling point,
- To be stored away from humidity,
- To be used at room temperature,
- Wear gloves and glasses for protection,
- Can damage paints and plastics.





TECHNICAL DATA

BARDAHL XBF DOT 4	Unit	Result	Method
Appearance	-	Amber	DIN 10964
Density at 20°C	Kg/m ³	1064	DIN EN ISO 12185
Kinematic viscosity at -40°C	mm ² /s	≤ 1500	DIN EN ISO 3104
Boiling point	°C	≥ 260 (265)	ISO 4925
Wet boiling point	°C	≥ 155 (165)	ISO 4925
Flash point	°C	> 110	DIN EN ISO 2719

RECOMMANDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

It is recommended to completely drain the brake system before using the brake fluid. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 24 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

24x250ML	5904
24x450ML	5914

