



Technos XFS A V504

DESCRIPTION

Technos XFS AV504 is a Premium Technology mid SAPS lubricant, for high efficiency, high-performance engines with low emissions. Dedicated to the latest generation of engines that require high performance lubricants of the VW 504.00 / 507.00, ACEA C3 and PORSCHE C30 level.

The precious synthetic bases and the special high shear stability polymers employed in the formula give Technos XFS extraordinary properties of resistance against thermal deterioration due to oxidation, of strength of the lubricating oil veil and of fluidity at low temperatures.

Bardahl XFS technology - eXtra Fluid Shield - gives the lubricant an additional reserve of performance in terms of reduction of the friction coefficient, protection against wear and deposit control, while ensuring the prolonged efficiency of the exhaust after-treatment systems and the increase of the fuel economy.

XFS technology Low Ash supplementary additive, developed specifically for the latest generation engines, offers maximum compatibility with exhaust after-treatment systems. It improves oxidation resistance, inhibits the formation of deposits, contains anti-wear, anti-scuffing and anti-friction agents.

XFS, eXtra Fluid Shield, intervenes as one extra shield, to protect all lubricated components and to maintain engine performance over time.

Technos XFS AV504 is suitable to be used in all those applications for which the manufacturer prescribes lubricants of the BMW LL-04 and MB 229.51 level.

PROPERTIES

- Maximises engine performance.
- Greater longevity and cleanliness of all engine parts.
- Safeguard the functionality of particle filters and catalytic converters.
- Easy starting and immediate lubrication at low temperature.
- Maximum extension of oil change intervals.
- 100% synthetic formula.





SPECIFICATIONS

Technos XFS AV504 0W-30

ACEA C3 / VW 504.00-507.00 / Porsche C30

SUITABLE FOR USE

BMW LL-04 (N20 Performance) / MB 229.51

Technos XFS AV504 5W-30

ACEA C3 / API SN / BMW LL-04 (N20 Performance) / VW 504.00-507.00 / Porsche C30 / MB 229.51

TECHNICAL DATA

	0w30	5w30
Viscosity at 40°C	65.01	70.05
Viscosity at 100°C	12.44	11.80
Viscosity at 15°C	0,844	0.852
Viscosity Index	193	165
Flash point	196	193
Pour Point	-48	-48
T.B.N.	9	9

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

0w30	
369040	24x1L
369053	60L
369054	200L
5w30	
308040	12x1L
308053	60L
308054	200L



NOTHING WILL STOP YOU

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahlois.com