



# XTM TRUCKS 15W40

## DESCRIPTION

Mineral engine oil for passenger cars, delivery vans, trucks, busses and public work equipment. Reduces significantly the deposits, provides anti-wear properties and contains strong cleaning additives. Meets the requirements of Euro 2, 3 and 4 norms.

## APPLICATION

**Bardahl XTM Trucks 15w40** extends the drain intervals. Compatible with EGR and SCR (reduction of NOx) systems. For long routes.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	E7
API	CI-4/SL
MB	228.3
RENAULT VI	RLD-2
DEUTZ	DQC III-10
VOLVO	VDS-3
MACK	EO-N/EO-M Plus
MAN	M3275-1
MTU	Type 2
CUMMINS	CES 20077/ 20078
GLOBAL	DHD-1
CAT	ECF-1a/ ECF-2
DETROIT DIESEL	93K215
JASO	DH-1



**NOTHING WILL STOP YOU**

SADAPS BARDAHL ADDITIVES & LUBRICANTS  
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2  
T: (+32) (0) 69 59 03 60

[www.bardahl.fr](http://www.bardahl.fr)  
[www.bardahloils.com](http://www.bardahloils.com)



## PROPERTIES

- ✓ Avoids deposits on pistons,
- ✓ Provides excellent cleaning and dispersing properties,
- ✓ Has a good thermal stability,
- ✓ Offers anti-wear properties.

## TECHNICAL DATA

Density at 20°C	Kg/l	0,888
Viscosity at -20°C	cP	6300
Viscosity at 40°C	mm <sup>2</sup> /s	110
Viscosity at 100°C	mm <sup>2</sup> /s	14,5
Viscosity Index		138
Flash point COC, °C	°C	214
Sulphated ash contents	%	1,3
TBN	mgKOH/g	10,3

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36062	20 L
36079	60 L
36077	205 L