



XBF DOT 4+ Class 6 BRAKE FLUID

DESCRIPTION

Fully synthetic brake fluid, high performance, formulated from glycol ethers.

APPLICATION

BARDAHL XBF DOT4+ meets all the international requirements mentioned below.

It is formulated to ensure good safety and protection of modern brake systems with ABS, ESP, DSC, etc.

Thanks to its good technical specifications, BARDAHL XBF DOT4+ is a high-quality brake fluid and can be used universally in brake systems from new generations.

The combination of special additives and its low viscosity ensure a better efficiency than DOT4, for complex brake and driving assistance systems. XBF DOT4+ offers a faster response time.

Has a very good chemical stability for a better safety.

Miscible with DOT4 or DOT 5.1, **but cannot be used with silicone-based fluid.**

SPECIFICATIONS

FMVSS 116	DOT 4
ISO	4925 Class 6
SAE	J1703

CLASSIFICATION

- ✓ Very high performance liquid, with high boiling point,
- ✓ To be stored away from humidity,
- ✓ To be used at room temperature,
- ✓ Wear gloves and glasses for protection,
- ✓ Can damage paints and plastics,
- ✓ Low viscosity.





TECHNICAL DATA

BARDAHL XBF DOT 4+	Unit	Result	Method
Appearance	-	Ambre	DIN 10964
Density at 20°C	Kg/m3	1052	DIN EN ISO 12185
Kinematic viscosity at -40°C	mm2/s	≤ 675	DIN EN ISO 3104
Boiling point	°C	≥ 267	ISO 4925
Wet boiling point	°C	≥ 172	ISO 4925
Flash point	°C	> 110	DIN EN ISO 2719

RECOMMANDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

It is recommended to completely drain the brake system before using the brake fluid. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 24 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

24x250ML	5902
24x450ML	5912